



## Comsafe PaperNorm Premium

**Certifications:** Certified & approved Class 0/N, EN 1143-1 / VdS 2450, Fire-rated EN-1047 (S-60P).  
**UK Cash Rating:** £ 6,000 Cash & £ 6,000 Content (Always check with your insurance company).



### Specifications:

- Burglary proof and fire resistant, double walled safe for valuables and documents (60 minutes for paper);
- Fire resistant seal in door-opening;
- Contents protected against fire & water;
- Total thickness door 110 mm;
- Sliding locking bolts on all 4 sides;
- Outside hinges (door opens 180 °);
- Lock protected against drilling;
- Safes are able to be secured to floor (1 hole);
- High-quality chrome Comsafe metal trimmings;
- Colour: white-aluminium (RAL 9006).



Picture: PaperNorm.

### Standard Lock (DB-lock):

- Double-bitted security key lock (2 keys supplied), EN 1300 Class A certified.

### Optional:

- Telescopic – pull out - shelves;
- Telescopic filing frame for suspension files;
- Electronic lock (**EL-lock**), no mechanical emergency opening, EN 1300 Class B certified.
- Interior safe 200 or 250 mm (Height).
- Mechanical combination lock (**MC-lock**), certified EN 1300 Class A.

### Lock variations:

		
High security DB lock EN 1300 Class A.	High security EL lock EN 1300 Class B (no mech. emergency opening).	Mechanical combination lock EN 1300 Class A.

Model	Art. Nr. DB	Art. Nr. EL	Art. Nr. MC	Exterior dim. HxWxD (mm)	Interior dim. HxWxD (mm)	Door-opening (HxW)	Kg	Shelf	# of Bolts	Ltr
Papernorm 65 Premium	T04927	T04928	T04929	636x600x480	536x500x308	490x454	180	2	8	82,5
Papernorm 120 Premium	T04930	T04931	T04932	1200x700x480	1100x600x308	1054x554	330	3	12	203
Papernorm 150 Premium	T04933	T04934	T04935	1550x700x480	1450x600x308	1402x554	410	3	12	268

(\*): Exterior Depth + 60 mm because of fittings.

Specifications are subject to change (06.2010).